

EDWARD A. VAREL
WILLIAM J. BESWICK

HBJ/HAS/dlj

REMOVABLE MORTAR MIXER BEARING AND SEAL ASSEMBLY

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to a bearing and seal assembly for supporting and sealing end portions of a rotatable paddle shaft in a mortar mixer or a mixer for similar abrasive materials and the like. More specifically, the bearing and seal assembly of the present invention represents an improvement over the bearing and seal assembly disclosed in U.S.

Patent No. 3,932,006, owned by the assignee of the present application.

2. Description of the Prior Art

U.S. Patent No. 3,932,006, issued January 13, 1976,
discloses a paddle shaft bearing and seal assembly supporting the
ends of the pivotal mixer drum and supporting and sealing the
paddle shaft ends which extend through openings in the end walls of
the mixer drum. The mortar or similar abrasive material being
mixed in the drum has a tendency to cause wear and deterioration of
the seal assembly with resultant migration of the abrasive material
into the interior of the bearing and seal housing and into the
bearings thus causing rapid wear of the bearings.

As disclosed in the aforementioned patent, each bearing
and seal housing is welded or otherwise permanently attached to the
outside surface of the mixer drum end wall. In use of the bearing
and seal assemblies disclosed in the above patent, the mixer
usually is operated until the seal subassemblies became worn and
fail permitting mortar or similar abrasive material to cause wear
of the bearings and ultimate seizure of the paddle shaft. In some
instances, this seizure requires that the paddle shaft be cut to
facilitate removal of the paddle shaft from the drum and subsequent
removal of the bearing and seal assemblies to enable replacement.

The prior U.S. patents cited in the specification of the above patent and the prior art cited in the "references cited" section of the above patent also disclose various bearing and seal structures for various rotatable components including seals for use in mixers.

5 Prior commercial mortar mixers with rotating paddle shafts also include some paddle shaft bearing and seal assemblies in which the housings are removable. However, such assemblies do not include a simple and effective bearing and seal assembly which can be easily lubricated or a removable bearing and seal housing which can be readily removed from the end wall of the drum. The prior art also does not utilize a removable bearing and seal housing supporting the bearing and seal subassemblies in a spaced relation with the bottom of the bearing and seal housing in alignment with the space between the bearing and seal subassemblies having an/ downwardly directed opening. Such an opening allows abrasive material which migrates past the seal subassembly to fall through the opening prior to such material reaching the bearings thereby increasing the life expectancy of the bearings and alerting the operator to seal failure which enables replacement of the bearing and seal assembly prior to the bearings failing due to contamination by the abrasive material migrating past the seal subassembly.

SUMMARY OF THE INVENTION

5 The paddle shaft seals and supporting bearings for each end of the paddle shaft and the pivotal mixing drum of the present invention are oriented in a bearing and seal housing which is removably attached to the outside surface of the mixer drum end wall by a plurality of removable bolts. This ability to unbolt and remove the bearing and seal housing on both ends of the drum allows the shaft to then be easily removed. In prior art designs where the housings are fixed in place on the outside of the drum, the shaft had to be passed through the bearings. This arrangement proved extremely difficult and often resulted in the shaft having to be cut and replaced, especially in those circumstances where the paddle shaft and bearings seized due to contamination of the bearings by abrasive material migrating past the seal subassembly. In accordance with the present invention, the bearing and seal housing can be removed from the ends of the shaft, thus making shaft removal much easier and replacement of the seals and bearings done much faster. As a result, substantial benefits are achieved in minimizing down time and in time and labor savings. Also, material savings can result by not having to destroy the shaft in the event of seizure.

Further, the removable bearing and seal housing of the present invention includes a pull ring or shoulder formed on the

outer cylindrical surface of the housing. The pull ring or shoulder on the outside of the housing allows for standard commercial bearing pullers to be used to remove the entire bearing and seal assembly from the paddle shaft end even in difficult circumstances as when the shaft has seized in the bearing and seal assembly. The pull ring facilitates the easier removal of the housing without unnecessary damage to the housing. Prior art designs required the forced extraction of the bearing from the housing. Such forced extraction often led to damage of the internal surface of the housing. Further, the easier removal of the housing results in further time, labor and material savings.

The removability of the bearing housing enables easier service and replacement of the bearings and seals when they become worn. Also, bearing and seal housings each including new bearing and seal subassemblies can be stocked as a replacement unit to enable quick field replacement by merely unbolting and pulling the bearing and seal housing with the worn bearings and seals and bolting on a replacement bearing and seal housing which includes new bearing and seal subassemblies.

Also, in accordance with the present invention, the bearing and seal subassemblies are oriented in the removable housing in a longitudinally spaced relation. This separation of the seals in relation to the bearings provides a space to receive

the mortar or other abrasive material which migrates out of the mixing drum past the seals. The bearing and seal housing also includes a large bottom opening in communication with the space between the seals and bearings so that any material which migrates past the seals will fall downwardly out ^{through} ~~through~~ the enlarged opening prior to the material contaminating the bearings. The escape of the migrating abrasive material from inside the housing protects the bearings from abrasive material and increases the life expectancy of the bearings.

10 The provision of the enlarged opening in the bearing and seal housing according to the present invention enables any material that migrates past the seal subassembly to fall through the opening to the ground or other surface area below the bearing and seal assembly. In addition to prolonging the life of the bearing by decreasing exposure to contamination, the material falling through the opening in the bearing and seal housing will serve as a visual indicator to the operator of the mixer that the seals needs replacing. Replacement can be efficiently accomplished by removing the bearing and seal housing from the end wall of the drum by the puller which then enables replacement of the seal subassembly without having shaft failure due to seizure of the bearings and paddle shaft during a mixing job thereby reducing down time and increasing efficiency.

Accordingly, an object of the present invention is to provide a bearing and seal assembly for the paddle shaft of a mortar mixer in which the bearing and seal housing is detachably mounted on each end wall of the mixer drum. Removal of the bearing and seal housings from the end walls of the drum results in substantial reduction in labor and time inasmuch as replacement of the bearing and seal assemblies can be accomplished much faster with substantial savings in repair costs, and the shaft does not have to be destroyed by cutting and removing the seized bearings and shaft which frequently becomes necessary when the mixer is operated until the shaft and bearing seize.

Another object of the present invention is to provide a bearing and seal assembly for the paddle shaft of mortar mixers or the like which enables easy removal of the shaft by providing a bolted, removable bearing and seal housings on each end wall of the mixer drum. By unbolting the bearing and seal housings and sliding the bearing and seal housings and bearing and seal subassemblies off of the shaft, the shaft can be easily removed from the mixer drum.

A further object of the present invention is to provide a mixer shaft bearing and seal assembly in accordance with the preceding objects in which the bearing and seal housing includes an external projecting pull ring or shoulder which enables

conventional bearing pullers to be utilized for bearing housing removal thereby providing an efficient and effective procedure for removing the bearing and seal assemblies from the mixer shaft end without damaging the housing.

5 A still further object of the present invention is to provide a bearing and seal assembly for the paddle shaft of a horizontal drum-type mixer in which extended bearing life is obtained by providing an increased separation of the bearings from the seals which insures that more operation time is permitted before the bearings can become contaminated resulting in longer operation time and productivity.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
10240
10245
10250
10255
10260
10265
10270
10275
10280
10285
10290
1

lower portion of the bearing and seal housing in alignment with and in communication with an increased space between the bearing and seal subassemblies. The vent opening allows any material which may migrate past the seals to fall downwardly onto the ground surface or other lower surface area not only to prevent contamination of the bearings but also indicate to a mixer operator that the seals have failed in order that prompt maintenance can be initiated to save the bearings and replace the seals.

Additional objects of this invention to be specifically enumerated herein is to provide a mortar mixer bearing and seal assembly in accordance with the preceding objects and which will conform to conventional forms of manufacture, be of simple construction and easy to use so as to provide an assembly that will be economically feasible, long lasting and relatively trouble free in operation.

These together with other objects and advantages which will become subsequently apparent reside in the details of construction and operation as more fully hereinafter described and claimed, reference being had to the accompanying drawings forming a part hereof, wherein like numerals refer to like parts throughout.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a fragmental perspective view of an end portion of a mortar mixer drum, supporting pedestal and trunnion cup and a bearing and seal assembly in accordance with the present invention.

Figure 2 is an elevational end view of the end of the mixer drum and the bearing and seal assembly of the present invention associated therewith, with the pedestal and trunnion cup removed.

Figure 3 is a sectional view, on an enlarged scale, taken along section line 3-3 on Figure 1 illustrating the specific structural details of the bearing and seal assembly of the present invention and its association with the mixer drum and trunnion support.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Although only one preferred embodiment of the present invention is explained in detail, it is to be understood that the embodiment is given by way of illustration only. It is not intended that the invention be limited in its scope to the details of construction and arrangement of components set forth in the following description or illustrated in the drawings. Also, in describing the preferred embodiment, specific terminology will be

resorted to for the sake of clarity. It is to be understood that each specific term includes all technical equivalents which operate in a similar manner to accomplish a similar purpose.

Referring to the drawings, the bearing and seal assembly of the present invention is generally designated by reference numeral 10. The overall assembly 10 includes a bearing subassembly generally designated by reference numeral 11 and a seal subassembly generally designated by reference numeral 12. The bearing subassembly 11 and seal subassembly 12 support and seal each end of a paddle shaft 14 in a mixer drum 16 having end walls 18. The paddle shaft 14 is rotatably driven and includes paddles (not shown) which mix mortar, plaster or similar abrasive materials. The mixer drum 16 can be pivoted about the axis of the paddle shaft 14 to discharge the mixed contents from the open upper end 20 of the drum 16 in a manner well known in the art.

Each end wall 18 of the drum 16 is provided with an opening 22 through which the paddle shaft 14 extends. The seal subassembly 12 is oriented against the outer surface of the end wall 18 and engages the peripheral surface of the paddle shaft 14 to prevent migration of abrasive material being mixed in the drum 16 along the surface of the paddle shaft 14 through opening 22 toward the bearing subassembly 11.

The bearing subassembly 11 and the seal subassembly 12 are supported in a removable bearing and seal housing 24 of generally cylindrical configuration and provided with a central bore defining a space 26 between the housing 24 and the periphery of the paddle shaft 14. The seal subassembly 12 is mounted in a recess 28 in the end of the housing 24 which faces and engages the end wall 18. The bearing subassembly 11 is supported in a cylindrical recess or bore 30 in the outer end of housing 24. As illustrated in Figure 3, the bearing recess or bore 30 is spaced from the seal assembly recess 28.

The bearing subassembly 11 is in the form of a sealed ball bearing unit having an outer race 32 engaging the recess 30, an inner race 34 engaged with the periphery of the paddle shaft 14 at an outer end thereof, and a series of ball bearings 35, as well known in the ball bearing art. The sealed ball unit 11 is a unitary subassembly commercially available from ball bearing manufacturers. The inner race 34 of the bearing subassembly 11 is engaged by a retaining washer 36. A retaining bolt 38 extends through washer 36 and is threaded into an internally threaded bore 40 in the shaft 14 as indicated by reference numeral 42. The retaining bolt 38 includes a retaining lock washer 74 with the retaining bolt 38, retaining washer 36 and lock washer securely retaining the bearing subassembly 11 assembled with respect to the

paddle shaft 14 and the bearing and seal housing 24 by maintaining the bearing unit 11 against a shoulder 44 forming on the inner end of the recess 30.

5 The end of the bearing and seal housing 24 which engages the outer surface of the end wall 18 is provided with a peripheral flange 46 which is detachably secured to the end wall 18 by a plurality of bolts 48 which extend through apertures 50 in the end wall 18 and apertures 52 in the flange 46. This structure secures the bearing and seal housing 24 detachably to the end wall 18 of the mixer drum 16. As shown in Figure 3, the head of bolts 48 are positioned inside the drum wall 18 and are secured outside the flange 46 by outwardly facing nuts 49 and washers 73 to facilitate the easy removal of nuts 49 and washers 73 and disengagement of the flange 46 and housing 24 from the drum wall 18.

10
15
20 The seal subassembly 12 includes a plurality of flexible seals 54 spaced apart by spacers 56. The seals 54 and spacers 56 have their outer edges received in the recess 28 in the housing 24 and completely fill the recess. The inner edges of the seals 54 are curved toward the interior of the drum 16 as indicated at reference numeral 58. The seals 54 are made of suitable flexible resilient material, preferably rubber, plastics such as urethane, or the like, and provide a long lasting and effective seal between the exterior surface of the paddle shaft 14 and the housing 24.

The innermost spacer of spacers 56 includes a slot 57 for passage of grease inserted through zerk or lubrication fitting 59 and a passage 61 in the wall of housing 24 and into the seal subassembly 12. By reason of the inward curve of the inner edges of the flexible seals 54, the grease inserted through slot 57 migrates toward the drum 16 and fills up the open spaces between the seals 54 before passing into the drum 16 itself.

The housing 24 includes an elongated arcuate slot-type vent opening 60 in the bottom of the housing which is aligned with and spaced below the enlarged space 26 between bearing subassembly 11 and seal subassembly 12. As such, any abrasive material that migrates from the interior of the drum 16 along the shaft 14 toward the bearings 35 as the seals 54 wear will enter elongated space 26 and fall through the elongated vent opening 60. This arrangement ensures that the abrasive material will not contaminate and cause excessive wear of the bearings 35. The abrasive material dropping through the opening 60 will fall to the ground surface or any other lower surface and provide an indication to the mixer operator that the seals 54 are worn and need replacement.

The bearing and seal housing 24 is supported by a trunnion cup 62 having a cylindrical portion 64 surrounding and journaling the outer end of the housing 24. The trunnion cup 62 includes an inwardly extending flange 66 which engages the end edge

of the housing 24 and extends inwardly past the outer race 32 of the bearing 10, as illustrated in Figure 3. The trunnion cup 62 is supported on a supporting bracket 68 which is rigidly connected to a bottom portion of the cup as by welding or the like. The bracket 68 in turn is attached to the upper end of a pedestal support 70 by bolts 71 to provide a rigid support for the trunnion cup 62. The trunnion cup 62 rotatably supports the outer end of housing 24 in order for the drum 16 to pivot to a position with the open upper end 20 downwardly inclined to dump the contents, such as into a conveyance for transport to a site of use of the mixed material in a manner well known in the art. A zerk or lubrication fitting 72 is provided on the upper portion of the trunnion cup 62 to lubricate the surfaces of the housing 24 and trunnion cup 62 when the housing 24 along with the drum 16 is pivoted between the mixing position and dumping position.

The external surface of the housing 24 is provided with a peripheral ring or shoulder 25 in a middle area thereof which projects outwardly therefrom. The ring or shoulder 25 is preferably continuous around the periphery of the housing 24 except for that area occupied by the arcuate slot opening 60. The ring or shoulder 25 enables a conventional bearing puller to be utilized in removing the bearing subassembly 11 along with the housing 24 and seal subassembly 12 from the paddle shaft 14 after the nuts 49,

washers 73, retaining bolt 38, lock washer 74, washer 36, and the support trunnion cup 62 have been removed. The order of removing the nuts 49, retaining bolt 38 and washer 36, and support trunnion cup 62 is not important so long as they are all removed in order to
5 separate the bearing and seal assembly 10 from the shaft 14 by a conventional bearing puller. The puller engages with the rib or shoulder 25 and the end of the shaft 14 to exert axial pressure against the housing 24 and the bearing subassembly 11 to remove these components along with the seal subassembly 12 from the shaft
10 14.

The foregoing structure of the present invention enables a preassembled cartridge assembly including housing 24, bearing subassembly 11 and seal subassembly 12 to be retained in stock as a unitary assembly so that the entire bearing and seal assembly 10
15 can be removed and replaced when the quantity of material falling from the vent opening 60 indicates to the mixer operator that the seals 54 have been excessively worn. The structure of bearing and seal assembly 10 also enables replacement of the bearing and seal subassemblies 11 and 12 in an efficient and effective manner and
20 eliminates seizing of the paddle shaft with respect to the bearings 35 when the bearings becomes contaminated with abrasive material. This structure further enables the mixer to continue in operation until the operator of the mixer is informed regarding the condition

of the seals 54 by observing material falling downwardly from the vent opening 60. This positive indicator of seal wear enables an increase in operating time and productivity and materially reduces the down time of a mixer in view of the short time necessary to
5 replace worn seals by removing the housing 24 together with bearing and seal subassemblies 11 and 12 and then replacing these components with a new preassembled bearing and seal assembly.

The foregoing is considered as illustrative only of the principles of the invention. Further, numerous modifications and
10 changes will readily occur to those skilled in the art. For example, the pull ring or shoulder 25 need not be in the form of a pull ring, but could be in the form of spaced projections, or even notches in the side of the housing such as to receive and engage the ends of a conventional bearing puller to move the housing 24
15 and the bearing and seal subassemblies 11 and 12 laterally with respect to the shaft 14. As such, it is not desired to limit the invention to the exact construction and operation shown and described, and, accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the
20 invention.